

Package: listWithDefaults (via r-universe)

October 31, 2024

Type Package

Title List with Defaults

Version 1.2.0

Date 2017-06-07

Author Russell S. Pierce

Maintainer Russell S. Pierce <russell.s.pierce@gmail.com>

Description Provides a function that, as an alternative to base::list, allows default values to be inherited from another list.

URL <https://github.com/drknexus/listWithDefaults>

BugReports <https://github.com/drknexus/listWithDefaults>

License GPL-2

Suggests testthat, rmarkdown, covr

Imports assertthat

RoxygenNote 6.0.1

Repository <https://russellpierce.r-universe.dev>

RemoteUrl <https://github.com/russellpierce/listwithdefaults>

RemoteRef HEAD

RemoteSha 67fe9b82ebfe7d45fa00e076a460a78cf7d0e6dc

Contents

listWithDefaults	2
Index	3

listWithDefaults	<i>listWithDefaults</i>
------------------	-------------------------

Description

Takes arguments as `base::list` to create a list. If any arguments are present in `defaultList`, but absent in ..., then the values from `defaultList` are used.

Usage

```
listWithDefaults(..., defaultList = NULL)
```

Arguments

...	objects, <i>must</i> be named; alternatively a single argument may be provided in this position as a <i>named</i> list
defaultList	a <i>named</i> list containing the default values

Note

Argument order is not controlled. Non-default arguments come first in the order specified followed by all default arguments.

Examples

```
listWithDefaults(defaultList=list(a=2,b=2))
listWithDefaults(a=1,defaultList=list(a=2,b=2))
listWithDefaults(b=1,defaultList=list(a=2,b=2))
listWithDefaults(a=1,b=1,defaultList=list(a=2,b=2))
listWithDefaults(list(a=1),defaultList=list(a=2,b=2))
```

Index

`listWithDefaults`, 2